

C O M M E R C I A L H E A D S E T S



Airman® 750 Single-Sided



Airman® 750



5x5® Pro III

*FAA TSO
approved*

*Lightweight
comfort*

*Dependable
communications*

*Flexible boom
pivots to either
side of the head*

M O S T P O P U L A R F O R A R E A S O N

The Airman 750 has become the world's best selling lightweight commercial headset because it offers comfort and dependable communications. Recommended by pilots and manufacturers, this FAA TSO approved line of headsets continues to lead the way in commercial aviation. In addition to the Airman 750, the lightweight line includes the 5x5 Pro III, and the recently introduced Airman 750 Single Sided headset. Telex gives you the most options and choices to meet specific needs of individual pilots.

See reverse side for more information and complete specifications.



Lightweight

COMMERCIAL HEADSETS

Airman® 750



Telex Lightweight Commercial Headsets offer convenience, dependability and comfort through a wide range of styles to meet the specific needs of individual pilots.



Airman® 750
Single-Sided



5x5® Pro III

FEATURES

Airman® 750

- Miniature amplified noise cancelling electret mic provides superior 400 Hz hum rejection.
- Dual dynamic receivers include replaceable cushions that gently hug each ear (one receiver/cushion only on the Single-Sided version).
- FAA TSO approved.

5x5® Pro III

- Weight on head specs of only 2.2 oz (62.3 g).
- Soft headpad cushions and adjustable headband, for true lightweight comfort.
- Receiver features single pliable, soft eartip receiver.
- High quality electret mic has flexible boom and amplifier.
- Headband detaches for optional eyeglass or custom earmold wearing configurations.
- FAA TSO approved.

ORDERING INFORMATION

Description	Catalog No.
Airman® 750	64300-200
Airman® 750 Single-Sided	64300-300
5x5® Pro III	64000-100

HEADSET SPECIFICATIONS

All Airman 750 specs apply to both the dual and the single-sided versions, except where noted.

Headphone Sensitivity

(Ref. 0002 Dynes/cm² @ 1mW Input @ 1 kHz)

Airman 750: 90 dB
5x5 Pro III: 119 dB

Headphone Usable Frequency Response

Airman 750: 100 – 3000 Hz
5x5 Pro III: 100 – 3000 Hz

Headphone Impedance to Match Amplifier Output

Airman 750: 150 – 600 ohms
Airman 750 Single-Sided: 150 ohms
5x5 Pro III: 150 – 600 ohms

Headphone Plug

Airman 750: 2 conductor .250" (6.3 mm) Diameter
5x5 Pro III: 2 conductor .250" (6.3 mm) Diameter

Microphone Type

Airman 750: Electret
5x5 Pro III: Electret

Microphone Frequency Response

Airman 750: 300 – 5000 Hz
5x5 Pro III: 100 – 10000 Hz

Microphone Output (nom.)

(@ 1 kHz 12 vdc 150 ohm load re: 1 microbar)
Airman 750: -50 db
5x5 Pro III: -48 dB

Microphone Impedance to Match Radio Input

Airman 750: 50 – 600 ohms
5x5 Pro III: 50 – 600 ohms

Microphone Plug (PJ-068) Equivalent

Airman 750: 3 conductor .206" (.523 mm) Diameter
5x5 Pro III: 3 conductor .206" (.523 mm) Diameter

Cord Extended Length and Style

Airman 750: 6' (1.8 m) Straight
5x5 Pro III: 6' (1.8 m) Straight

Weight (without cord)

Airman 750: 3.2 oz (90.7 g)
Airman 750 Single-Sided: 2.4 oz (68 g)
5x5 Pro III: 3.8 oz (107.7 g)

Distributed by

TELEX®

Telex Communications, Inc.

12000 Portland Ave. So., Burnsville, MN 55337 USA
Toll-Free 1-877-863-4168; 952-887-5510, Fax: 952-887-5595

E-Mail: aircraft@telex.com Web: www.telex.com/aircraft